



## BACKGROUND OF THE INVENTION

### I. Field of the Invention

This invention relates to loudspeakers for music systems. More particularly, this invention relates to loudspeakers which may be water cooled to provide higher sound quality.

Conventional loudspeakers (speakers) used in modern music systems must be capable of producing high sound quality at many different power levels. Speakers typically include a permanent magnet for generating a magnetic field and a yoke assembly. The yoke assembly has a T-yoke, and a magnet / plate pieces for focusing the magnetic field to an air gap in which the field is particularly intensified. A voice coil is suspended in the air gap so as to be capable of vibrating. A current is passed through the voice coil and the interaction of the magnetic field induced by the current and the field from the permanent magnet causes the voice coil to vibrate. The voice coil is connected to a speaker cone which has a large surface area to vibrate air in the vicinity of the cone and thus produce sound.

One factor which adversely affects the life of the speaker is excessive heat generated in the voice coil. This heat is mainly caused by the inherent impedance of the wire in the voice coil. The voice coils in speakers have a typical operating temperature range of approximately 150° F to 200° F. When the voice coil begins to significantly exceed the range, for example approximately 300° F, the voice coil may be damaged. This damage could include the coil windings becoming de-laminated from the former or the adhesive between various other speaker parts breaking down. Such damage may cause outright speaker failure or at the very least, substantial shortening of the effective life of the speaker. Another problem caused by excessive heating is an increase in impedance in the voice coil which reduces the amount of power converted to sound. Of course, the increasing impedance is self-perpetuating in that a higher impedance results in more heat

which in turn creates still higher impedance. While attempts have been made in the prior art to induce some air flow cooling within the speaker, this mechanism is generally insufficient to provide the cooling needed to prevent damage to the voice coil.

What is needed in the art is a speaker which can be efficiently constructed and operated to accomplish water (or other liquid) cooling of a speaker.

## **II. Objects and Summary of Invention**

It is therefore an object of this invention to provide an improved speaker which substantially reduces the amount of heat to which the voice coil is exposed.

It is a further object to provide a speaker which includes a liquid cooling mechanism.

It is a further object to provide a fluid cooled T-yoke which will cool a speaker of which the T-yoke is an element.

Therefore the present invention provides a fluid cooled speaker having a T-yoke with a pole piece, a magnet surrounding the pole piece, a voice coil positioned between the pole piece and the magnet, and a cone connected to the voice coil. The T-yoke includes a body having a base and a pole piece with a sealed cavity formed within the pole piece. The T-yoke also has a fluid inlet and outlet formed in the body and communicating between the cavity and an area outside the body of the T-yoke.

## **III. Brief Description of the Drawings**

Figure 1A is a cross-sectional view of a typical prior art speaker having a non-vented T-yoke.

Figure 1B is a cross-sectional view of a typical prior art speaker having a vented T-yoke.

Figure 2 is an exploded view of a typical prior art speaker.

Figures 3A-3D represent one embodiment of the fluid cooled T-yoke and speaker of the

present invention.

Figures 4A-4C represent an alternate embodiment of the fluid cooled T-yoke and speaker of the present invention.

Figures 5A-5C represent another alternate embodiment of the fluid cooled T-yoke and speaker of the present invention.

Figures 6A-6C represent another alternate embodiment of the fluid cooled T-yoke and speaker of the present invention.

Figures 7A-7D illustrate still another embodiment of the fluid cooled T-yoke and speaker of the present invention.

Figure 8 represents the speaker of the present invention connected to a typical fluid cooling system.

#### **IV. Detailed Description of the Invention.**

Figure 1A illustrates a cross-sectional view of prior art speaker 1 while Figure 2 is an exploded view of speaker 1. Speaker 1 is formed from a basket 8 with a cone 4 positioned therein. Cone 4 terminates on the upper perimeter of basket 8 with an edge roll 3 and a top gasket 2 helping to secure cone 4 in basket 8. It can be seen how cone 4 is connected at its lower perimeter to voice coil former 10. Voice coil former 10 will included a cylindrical tubular member constructed of a material such as aluminum and will have voice coil formed by numerous turns of electrical wiring (normally copper or aluminum) wrapped around the former tube. As used herein, the term "voice coil" may be used to refer either to the former with the wire voice coil wrapped thereon or simply the coil of wiring itself. A dust cap 5 will be positioned on voice coil 10.



design may provide some cooling effect of T-yoke 15, the heat transfer rate between T-yoke 15 and air is significantly less than the heat transfer rate between a T-yoke and a circulating liquid.

Figures 3A-3D provide one preferred embodiment of the present invention, liquid cooled T-yoke 25. T-yoke 25 will generally comprise a pole piece 26 and a base 27. Figure 3B illustrates how an interior cavity 33 will be formed in pole piece 26. A threaded base aperture 28 communicating with cavity 33 which will be formed in base 27. Figure 3B also illustrates a base plug 30 having threaded surface 31 and barbed hose fittings 32 extending from fluid inlet 34 and fluid outlet 35. Base plug 30 also has an extension tube 36 extending above the height of threaded surface 31. While extension tube 36 is shown connected to inlet 34, it will be understood that extension tube 36 could just as readily be attached to outlet 35. Figure 1C best illustrates how base plug 30 will further include a polygonal gripping surface 38 adapted for application of a wrench or similar tool. Figure 1D illustrates how base plug 30 will be inserted into threaded base aperture 28 of T-yoke 25 and form a fluid tight seal between base aperture 28 and plug 30. When base plug 30 is inserted into T-yoke 25, extension tube 36 will be positioned in the upper portion 37 of cavity 33. In this manner, extension tube 36 helps insure that fluid will circulate through all portions of cavity 33 and effect the greatest heat transfer.

An alternate embodiment of the T-yoke is seen in Figures 4A-4C. T-yoke 40 differs from the previous embodiment in that the water circulating cavity is formed by way of two intersecting passages 42 being drill through base 47 into the interior of pole piece 46. Threaded fluid hose fittings 41 may then be inserted into passages 42 in order to form a fluid inlet and outlet through fittings 41. Again hose fittings 41 have barbs which aid in retaining the hose on fittings 41.

A still further embodiment is seen in Figures 5A-5C. Here, the fluid cavity is formed (as best seen in Figure 5C) by drilling two vertical passages 55 through base 57 and into pole piece



in the drawings, cup insert 82 could alternatively be formed without a threaded outer surface 86, but sized to create a tight friction fit within vent aperture 19. Cup insert 82 could then be pressed into place within vent aperture 19. Fitting plug 81 could also be formed without threaded collar 87. The base opening 88 on cup insert 82 could then be formed with an extended lip which would be rolled over the bottom of fitting plug 81 once fitting plug 81 was pressed into base opening 88.

Fitting plug 81 will include two hose fittings 89 which form fluid inlet 34 and outlet 35 and fitting plug 81 will further include a divider wall 85 (best seen in Figure 7D) positioned above and between inlet 34 and outlet 35. Figure 7D first illustrates fitting plug 81 with divider wall 85 seen from the side and further illustrates fitting plug 81 rotated 90° to show divider wall 85 from the front perspective. Figure 7C demonstrates how sleeve cup insert 82 will be threaded into aperture 19 and fitting plug 81 threaded into base opening 88. In this configuration, the T-yoke 15 becomes mechanically equivalent to the previously disclosed embodiments of the T-yoke which had cavities formed directly in the pole piece. As shown by Figure 7C, cooling fluid will enter cavity 84 through inlet 34, circulate around divider wall 85 and exit outlet 35. As seen in Figure 7D, divider wall 85 has a width "w" which will be approximately the width of cavity 84. It is not necessary that divider wall 85 form a seal with the sides of cavity 84. It is only necessary that divider wall 85 is wide enough to direct a substantial portion of the cooling fluid entering cavity 85 over the top of divider wall 85 as opposed to around its sides. It will be understood that divider wall 85 performs the same function as extension tube 36 (seen in Figure 3B) in that it forces fluid circulation in the upper portion of the cavity 85. Preferably, cup insert 87 will be constructed of a highly conductive material, such as metal (aluminum, iron, etc.), so that cup insert 87 will readily conduct heat from T-yoke 15 and allow transfer of the heat to fluid circulating through cavity 84.



Figure 8 illustrates one embodiment of the fluid cooling system which will circulate cooling fluid to the fluid cooled speaker of the present invention. Speaker 1 is illustrated with the T-yoke 25 of the present invention. Heat from voice coil 10 will be transferred to T-yoke 25 and then to the fluid in cavity 33. The fluid in cavity 33 is circulated from outlet 35 to heat exchanger 76 by pump 75. As the fluid flows through heat exchanger 76, heat will be dissipated to the surrounding environment by vanes 77 on heat exchanger 76. The cooled fluid will then be circulated back to cavity 33 by way of inlet 34. It will be understood that Figure 8 is illustrative of only one basic fluid cooling system. The system could also include a separate fluid reservoir integrated therein. Additionally, various types of conventional heat exchange mechanisms could be employed, including eliminating the heat exchanger 76 and allowing the heat transfer to occur in a fluid reservoir. There are also a large variety of fluids which could be used to cool the present invention. These fluids include water, glycol, a water/glycol mixture and numerous oils.

Although certain preferred embodiments have been described above, it will be appreciated by those skilled in the art to which the present invention pertains that modifications, changes, and improvements may be made without departing from the spirit of the invention defined by the claims. All such modifications, changes, and improvements are intended to come within the scope of the present invention.